

Bagging Machine PACKMAT TYP SD

Features

- ▶ Inclined bagging machine
- ▶ Application: Packing of individual parts or bulk goods
- ▶ Processing of flat film (PE, PP, composite film)
- ▶ Sealing system: digitally controlled
- ▶ Wheeled machine frame
- ▶ Electric controls: VIPA 300 SPEED 7 or SIEMENS S7-300
- ▶ Operating unit: SIEMENS, Touch-Panel coloured display
- ▶ 3 Password levels for access rights
- ▶ Software with graphical input masks
- ▶ Fault indication by Clear Text
 - ▶ Menu management of the machine parameters
 - ▶ Data-Communication: Ethernet-Connection
 - ▶ Synchronized ready for additional machines
- ▶ Design in accordance with:
 - ▶ DIN EN 60204-1 (VDE113-1/A1:2009-10)
 - ▶ Machinery Directive standards 2006/42/EG
 - ▶ Customers factory standards (on request)
- ▶ Low maintenance effort

Options

- ▶ Manual infeed:
 - ▶ Hand-Working-Table, Counting-Weighing-Table
- ▶ Automatic infeed:
 - ▶ Counting-, Weighing-, Assembly-machines
 - ▶ Thermotransfer-Direct-Printer, Label applicator
 - ▶ Linked bag chain
 - ▶ Longitudinal- and transversal perforation device
 - ▶ Clean room design
 - ▶ Euro hole punch unit
 - ▶ Servo drive
 - ▶ Center folded film
 - ▶ Other options on request



Technical Data

Cycle speed:	up to 50 Bags / min (depending on bag length, product weight, infeed rate and options)
Bag width:	to 280, 350, 450mm (dependent machine type)
Bag length:	dependent machine type, directly adjustable
Passage Clearance:	up to 90, 130, 180mm (Special measures on request)
Film thickness:	40 – 180 µm
Electric supply:	230/400 V, 50/60Hz
Compressed Air:	min. 5 bar (oil-free)
Dimension:	for F280SD 1500 x 1300 x 1700mm (L x W x H)
Weight:	for F280SD 200 kg

PACKMAT® Maschinenbau GmbH

Gewerbestraße 4
D-78667 Villingendorf

Tel.: +49 (0)741 9281 - 0
Fax: +49 (0)741 9281 - 900

info@packmat.de
www.packmat.de