

## Bagging Machine PACKMAT TYP VD

### Features

- ▶ Vertical bagging machine
- ▶ Application: Packing of individual parts or bulk goods
- ▶ Processing of flat film (PE, PP, composite film)
- ▶ Sealing system: digitally controlled
- ▶ Wheeled machine frame
- ▶ Electric controls: VIPA 300 SPEED 7 or SIEMENS S7-300
- ▶ Operating unit: SIEMENS, Touch-Panel coloured display
- ▶ 3 Password levels for access rights
- ▶ Software with graphical input masks
- ▶ Fault indication by Clear Text
  - ▶ Menu management of the machine parameters
  - ▶ Data-Communication: Ethernet-Connection
  - ▶ Synchronized ready for additional machines
- ▶ Design in accordance with:
  - ▶ DIN EN 60204-1 (VDE113-1/A1:2009-10)
  - ▶ Machinery Directive standards 2006/42/EG
  - ▶ Customers factory standards (on request)
- ▶ Low maintenance effort

### Options

- ▶ Manual infeed:
  - ▶ Hand-Working-Table, Counting-Weighing-Table
- ▶ Automatic infeed:
  - ▶ Counting-, Weighing-, Assembly-machines
  - ▶ Thermotransfer-Direct-Printer, Label applicator
  - ▶ Linked bag chain
  - ▶ Longitudinal- and transversal perforation device
  - ▶ Clean room design
  - ▶ Euro hole punch unit
  - ▶ Servo drive
  - ▶ Center folded film
  - ▶ Other options on request



Leaving technical changes © 2016 Packmat® Maschinenbau GmbH

### Technical Data

Cycle speed:	up to 50 Bags / min (depending on bag length, product weight, infeed rate and options)
Bag width:	to 280, 350, 450mm (dependent machine type)
Bag length:	dependent machine type, directly adjustable
Passage Clearance:	up to 90, 130, 180mm (Special measures on request)
Film thickness:	40 – 180 µm
Electric supply:	230/400 V, 50/60Hz
Compressed Air:	min. 5 bar (oil-free)
Dimension:	for F280VD 1200 x 1200 x 1800mm (L x W x H)
Weight:	for F280VD 200 kg

### PACKMAT® Maschinenbau GmbH

Gewerbestraße 4  
D-78667 Villingendorf

Tel.: +49 (0)741 9281 - 0  
Fax: +49 (0)741 9281 - 900

info@packmat.de  
www.packmat.de